

# Survey Returned Fields

Last Modified on 03/16/2017 11:28 am EDT |

Returned fields for the Survey object are explained below. Go to the [Example Returns](#) section to view return examples for each call type.

## Returned Fields for the Survey Object

Field	Description	Format
id	Survey ID	string
team	Team ID	string
_type	API object type	string
_subtype	Project type (Survey, Poll, Form, Quiz)	string
Status	Project status (Open, Closed)	string
created_on	Date/time created	YYYY-MM-DD HH:MM:SS
modified_on	Date/time last modified	YYYY-MM-DD HH:MM:SS
forward_only	Disables Back Button	boolean
languages	Array of translated languages	string
title	Project/Survey Title	string
internal_title	Internal Title	string
title_ml	Array of titles for each translation (ex: [English] => Survey Title, [Spanish]	string

Field	Description	Format
Links	Array of all share links	URL
Statistics	Array of response counts for each status e.g. partial, complete, etc.	array
theme	Theme ID	string
blockby	Duplicate protection type (IP, COOKIE, null)	string
pages	Array of survey pages. See SurveyPage Returned Fields for more info.	array

## Example Returns (.debug format)

- [GetList Return Example](#)
- [Get Survey Return Example](#)
- [Create Survey Return Example](#)
- [Update Survey Return Example](#)
- [Delete Survey Return Example](#)

GetList Return Example (.debug format):

Array

```
(
  [result_ok] => 1
  [total_count] => 5
  [page] => 1
  [total_pages] => 1
  [results_per_page] => 5
  [data] => Array
    (
      [0] => Array
        (
          [id] => 1357785
          [team] => 406258
          [_type] => Survey
          [_subtype] => Poll
          [status] => Launched
          [created_on] => 2013-09-07 19:55:22
          [modified_on] => 2013-09-07 19:55:23
          [title] => Poll
          [statistics] =>
            (
              [Complete] => 2
            )
          [links] => Array
            (
              [edit] => {edit link}
              [publish] => {publish link}
            )
        )
    )
)
```

GetSurvey Return Example (.debug format):

```

Array
(
    [result_ok] => 1
    [data] => Array
        (
            [id] => 1118412
            [team] => 406257
            [_type] => Survey
            [_subtype] => Survey
            [status] => In Design
            [created_on] => 2012-12-18 17:19:23
            [modified_on] => 2012-12-19 16:05:49
            [forward_only] =>
            [languages] => Array
                (
                    [0] => English
                )

            [title] => Survey
            [internal_title] => Survey
            [title_ml] => Array
                (
                    [English] => Survey
                )

            [theme] => 11147
            [blockby] => NONE
            [statistics] =>
            [links] => Array
                (
                    [edit] => {edit link}
                    [publish] => {publish link}
                )
        )
)

```

The remainder of the survey get object return is an array of survey pages.  
See the SurveyPage object for more.

**Create Survey Return Example (.debug format):**

```

Array
(
    [result_ok] => 1
    [data] => Array
        (
            [id] => 1120173
            [team] => 406256
            [_type] => Survey
            [_subtype] => Survey
            [status] => In Design
            [created_on] => 2012-12-20 16:03:16
            [modified_on] => 2012-12-20 16:03:16
            [forward_only] =>
            [languages] => Array
                (
                    [0] => English
                )

            [title] => My New Survey
            [internal_title] => My New Survey
            [title_ml] => Array
                (
                    [English] => My New Survey
                )

            [theme] => 11147
            [blockby] =>
            [statistics] =>
            [links] => Array
                (
                    [edit] => {edit link}
                    [publish] => {campaign link}
                )

```

The remainder of the survey create object return is an array of survey pages. See the SurveyPage object for more.

**Update/Copy Survey Return Example (.debug format):**

Array

```
(
  [result_ok] => 1
  [data] => Array
    (
      [id] => 1120161
      [team] => 406256
      [_type] => Survey
      [_subtype] => Survey
      [status] => In Design
      [created_on] => 2012-12-20 15:50:41
      [modified_on] => 2012-12-20 17:47:15
      [forward_only] =>
      [languages] => Array
        (
          [0] => English
        )

      [title] => Updated Survey
      [internal_title] => Updated Survey
      [title_ml] => Array
        (
          [English] => Updated Survey
        )

      [theme] => 11147
      [blockby] => COOKIE
      [statistics] =>
      [links] => Array
        (
          [edit] => {edit link}
          [publish] => {publish link}
          [campaign] => {campaign link}
        )
    )
)
```

The remainder of the survey update object return is an array of survey pages. See the SurveyPage object for more.

## Delete Survey Return Example (.debug format):

```
Array  
(  
  [result_ok] => 1  
)
```